





**Castel MAC SpA**

Via del Lavoro, 9 C.P. 172  
I - 31033 Castelfranco Veneto (TV)  
ITALY EU

Tel. +39 0423 738452  
Fax +39 0423 722811

icematic@castelmac.it  
www.castelmac.it

## Fabbricatore di ghiaccio in cubetti | Ice cubers | Eiswürfelerzeuger Machines à glace en cubes | Màquinas productoras de hielo en cubitos

I MODELLI E LE SPECIFICHE POSSONO ESSERE CAMBIATI IN QUALUNQUE MOMENTO SENZA PREAVVISO  
MODELS AND SPECIFICATIONS ARE SUBJECT TO BE CHANGED WITHOUT NOTICE  
WIR BEHALTEN DAS RECHT VOR JEDERZEIT ANDERUNGEN DER MODELLE UND DER TECHNISCHEN ANGABEN VORZUNEHMEN  
LES MODELES ET CARACTERISTIQUES DES APPAREILS PEUVENT ETRE CHANGES SANS PREAVIS  
LOS MODELOS Y LAS ESPECIFICACIONES PODRAN MODIFICARSE EN CUALQUIER SIN PREVIO AVISO

# N202M

Produzione di ghiaccio in 24 ore fino a  
Ice produced for 24 hours up to  
Eisproduktion in 24 Stunden bis zu  
Production de glace en 24 h jusqu'à  
Produccion de hielo en las 24 horas hasta

kg. 240

PRODUZIONE DI GHIACCIO  
ICE PRODUCTION  
EIS PRODUKTION  
PRODUCTION DE GLACE  
PRODUCCION DE HIELO

Raffreddamento unità condensatrice Condensing unit cooling Kondensatoreinheit Refroidissement de l'unité de condensation Refrigeración de la unidad condensadora	aria air Luft air aire	o acqua: consumo n. 83 litri per ora* or water: consumption n. 83 litres per hour* oder Wasser: Verbrauch n. 83 liter pro Stunde* ou eau: consommation n. 83 litres par heure* o agua: consumo n. 83 litros para hora*
--	------------------------------------	--

**RAFFR. AD ACQUA / WATER  
COOLED / WASSERGEKÜHLT  
REFR. A EAU / REFR. A AGUA**  
Temperatura acqua/Water temperature  
Wassertemperatur/Température eau  
Temperatura agua

Potenza assorbita/Absorbed power/Leistungsaufnahme Puissance absorbée/Potencia Absorbida	W 1000 (aria/air) W850 (acqua/water)
---	---

°C	32°	21°	15°	10°	
10°	175	200	215	220	kg
21°	170	195	210	215	kg
32°	160	185	192	197	kg
38°	155	180	185	190	kg

Prod. ghiaccio in 24 h/Ice prod. per 24 h  
Eisprod. in 24 h/Prod. de glace en 24 h  
Prod. de hielo en 24 h

Refrigerante / Refrigerant / Kältemittel / Réfrigérant / Refrigerant	R 404a
--	--------

Attacco entrata acqua / Water inlet connection / Anschluss für Wasserzufluss Prise entrée d'eau / Conexión entrada agua	3/4" Gas
--	----------

Attacco scarico acqua / Water output connection / Anschluss für Wasserabfluss Prise écoulement d'eau / Conexión desague	mm. Ø 20
--	----------

Alimentazione monofase/Single phase input/ Einphasige Spannung/Alimentation monophasée Alimentación monofásica	220V-240V - 50 Hz
--	-------------------

Alimentazione voltaggi speciali: Extra voltages: Andere Spannungen: Alimentation voltages spéciaux: Otros voltajes especiales:	a richiesta on request Lieferbar auf Wunsch sur demande según pedido
--	--

Carrozzeria - External structure Ausführung - Carrosserie - Carroceria	inox
---	------

Peso netto/Net weight/Netto Gewicht Poids net/Peso neto	Kg. 70
--	--------

(\*) con temperatura acqua 15 °C  
with water temperature 15 °C  
mit Wassertemperatur 15 °C  
avec température eau 15 °C  
con temperatura agua 15 °C

### Dimensioni / Dimensions / Masse / Dimensions / Dimensiones

