

## P120E "C"

Modular electric oven for pizzeria

COMPOSITION WITH 3 BAKING CHAMBERS



### OPTIONS AND ACCESSORIES (WITH SURCHARGE)

- Support with wheels, height 600mm
- Additional tray holder guides for compartment and support
- Suction hood

### (WITHOUT SURCHARGE)

- Front vapour collection hood in stainless steel sheet

### EXTERNAL CONSTRUCTION

- Structure made in folded stainless steel
- Side panels in pre-painted sheet metal
- Stainless steel hood with aluminised steel top cover
- Front vapour collection hood in enameled steel sheet
- Steam duct in stainless steel plate
- Stainless steel double door with bottom hinge and spring balance
- Tempered glass element
- Handles in thermoplastic material
- Control panel on front right hand side

### INTERNAL CONSTRUCTION

- Refractory brick cooking surface
- Aluminated steel top and side structure
- Rock wool heat insulation

### FUNCTIONING

- Heated by armoured heating elements
- Electronic temperature management with independent adjustment of ceiling and floor
- Maximum temperatura reached 450°C
- Continuous temperature monitoring with thermocouple
- Vapour ducting using manual butterfly valve

### STANDARD EQUIPMENT

- Lighting with halogen lamp
- Timer
- Economiser
- Independent maximum temperature safety device
- 20 customisable programs



**MORETTI FORNI S.P.A.**

[www.morettiforni.com](http://www.morettiforni.com)

[info@morettiforni.com](mailto:info@morettiforni.com)


Via A.Meucci, 4 - 61037 Mondolfo (PU) ITALIA  
Tel. +39.0721.96161 - Fax +39.0721.9616299



## P120E "C"

### 3 baking chambers height 18cm

(assembled with support height 600mm)



**Note:** The dimensions indicated in the views are in millimeters. Steamer for Bakery only.

#### SPECIFICATIONS

The appliance comprises three independent cooking elements and an optional leavening compartment or support. The oven cooking surface is made of refractory, allowing perfect heat distribution over the whole surface and making this oven particularly suitable for use by pizza cooks. Temperature adjustment is electronic, with independent control of the ceiling and floor heating elements. The oven door is hinged at the bottom, with a tempered glass window to check the state of the product while it is cooking. The support comprises a painted metal structure, whereas the leavening compartment has a stainless steel structure and is fitted with a heating thermostat. The leavening compartment can reach a maximum temperature of 65°C, whereas the maximum temperature of the baking chamber is 450°C

All the data provided below refer to the configuration with 3 baking chambers

#### DIMENSIONS

External height	1550mm
External depth	1879mm
External width	1610mm
Weight	816kg
Baking surface	4,8m <sup>2</sup>

#### SHIPPING INFORMATION

Packed in wooden crate	
Height	1700mm
Depth	2052mm
Width	1810mm
Weight	(816+70)kg

#### FEEDING AND POWER

<i>Standard feeding</i>	
A.C. V400 3N	
<i>Feeding on request</i>	
A.C. V230 3	
Frequency	50/60Hz
Max power	46,5kW
Average power cons	23,2kWh
Connecting cable for each chamber	
type H07RN-F	
5x6mm <sup>2</sup> (V400 3N)	
4x10mm <sup>2</sup> (V230 3)	
Power supply (optional prover)	
A.C. V230 1N 50/60 Hz	
Max power	1,5kW
Average power cons	0,8kWh
Conn. Cable type	H07RN-F
3x1,5mm <sup>2</sup>	

#### TOTAL BAKING CAPACITY

When combined with leavening compartment or support:	
Tray (600x400)mm	18
Pizza diameter 300mm	48
Pizza diameter 450mm	18

Max height	2650mm
Max weight	(928+80)kg

\* This value is subject to variation according to the way in which the equipment is used

- NOTE: MORETTI FORNI S.P.A. reserves the right to modify the characteristics of the products illustrated in this publication without prior notice