

DATI TECNICI - SPECIFICATIONS

	COND.	COMP. W	ABS. W	FUSE	Kwh/100Kg	l/h	kg	Lbs	kg	Lbs
M402 A		4360	2100	16	13.1	19.0	88	194	106	234
M402 W		4360	1900	16	10.6	210	83	183	101	223



PRODUZIONE DI GHIACCIO - ICE PRODUCTION kg/24h - lbs/24h

210



Large Cube - 17 g
29 x 29 x 24 mm

342



Dice Cube - 10 g
22 x 22 x 24 mm

555



Half-Large Cube - 6 g
10 x 29 x 24 mm

Raffreddamento ad aria Air Cooled Unit

Temp. aria Air Temp. °C	Temp. acqua / Water Temp.			
	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	360	395	420	430
50°	794	871	926	948
21°	340	370	390	400
70°	750	816	860	882
32°	280	305	312	320
90°	617	672	688	705
38°	225	250	257	265
100°	496	551	567	584

Raffreddamento ad acqua - Water Cooled Unit

Temp. aria Air Temp. °C	Temp. acqua / Water Temp.			
	32°	21°	15°	10°
°F	90°	70°	60°	50°
10°	315	347	365	370
50°	694	765	805	816
21°	300	332	350	355
70°	661	732	772	783
32°	280	315	327	335
90°	617	694	721	739
38°	270	305	317	325
100°	595	672	699	716

DEPOSITO - SLOPE BIN

D205 - D255
D305(KM305)- D405(KFM404)-
D505(KFM505)

DIMENSIONI - DIMENSIONS

LxPxH(mm): 760 x 620 x 725
WxDxH(in): 29 15/16" x 24 7/16" x 28 9/16"



220-240/50/1



R404A

MIN

MAX

10°C (50°F)



40°C (104°F)

5°C (41°F)



35°C (95°F)

-10%



+10%

1 Bar (14 psi)






5 Bar (70 psi)

MARCHI - MARKS



CONTROLLO - CONTROL


	Alimentazione Powered
	In Funzionamento Operating
	Deposito Pieno/Lavaggio Storage Full / Washing
	Allarme Alarm
	Allarme Alta Pressione High Pressure Alarm
	Pulsante Reset/Lavaggio Button Reset/Washing




AIR COOLED

WATER COOLED

TOP VIEW



Back View



Back View

- A Water drain Ø20 mm
- B Potable water inlet 3/4 GAS
- C Electrical cable supply
- D Water cooled inlet 3/4 GAS
- E Water cooled outlet 3/4 GAS

