

DATI TECNICI - SPECIFICATIONS

| | COND. | COMP. W | ABS. W | FUSE | Kwh/100Kg | l/h | kg | Lbs | kg | Lbs |
|--------|-------|---------|--------|------|-----------|------|----|-----|-----|-----|
| M502 A | | 6629 | 2150 | 16 | 13.47 | 20.2 | 98 | 216 | 116 | 256 |
| M502 W | | 6629 | 1950 | 16 | 10.6 | 208 | 98 | 216 | 116 | 256 |



PRODUZIONE DI GHIACCIO - ICE PRODUCTION kg/24h - lbs/24h

| | | | | | | | | |
|------------|--|--------------------------------------|------------|--|-------------------------------------|------------|--|--|
| 210 | | Large Cube - 17 g 29 x 29 x 24 mm | 342 | | Dice Cube - 10 g 22 x 22 x 24 mm | 555 | | Half-Large Cube - 6 g 10 x 29 x 24 mm |
|------------|--|--------------------------------------|------------|--|-------------------------------------|------------|--|--|

DEPOSITO - SLOPE BIN

D205 - D255
D305(KM305)- D405(KFM404)-
D505(KFM505)

DIMENSIONI - DIMENSIONS

LxPxH(mm): 760 x 620 x 725
WxDxH(in): 29 15/16" x 24 7/16" x 28 9/16"



400V/50HZ/3



R404A

MIN

MAX

10°C (50°F)



40°C (104°F)

5°C (41°F)



35°C (95°F)

-10%



+10%

1 Bar (14 psi)



5 Bar (70 psi)

MARCHI - MARKS



CONTROLLO - CONTROL




| | |
|-----|---|
| | Alimentazione Powered |
| *** | In Funzionamento Operating |
| | Deposito Pieno/Lavaggio Storage Full / Washing |
| | Allarme Alarm |
| | Allarme Alta Pressione High Pressure Alarm |
| | Pulsante Reset/Lavaggio Button Reset/Washing |

Raffreddamento ad aria Air Cooled Unit

| Temp. aria Air Temp. | Temp. acqua / Water Temp. | | | |
|-------------------------|---------------------------|------------|------------|------------|
| °C | 32° | 21° | 15° | 10° |
| °F | 90° | 70° | 60° | 50° |
| 10° | 415 | 440 | 453 | 465 |
| 50° | 915 | 970 | 999 | 1025 |
| 21° | 385 | 410 | 425 | 431 |
| 70° | 849 | 904 | 936 | 950 |
| 32° | 307 | 341 | 353 | 364 |
| 90° | 677 | 752 | 778 | 802 |
| 38° | 276 | 307 | 316 | 326 |
| 100° | 608 | 677 | 696 | 719 |

Raffreddamento ad acqua - Water Cooled Unit


| Temp. aria Air Temp. | Temp. acqua / Water Temp. | | | |
|-------------------------|---------------------------|------------|------------|------------|
| °C | 32° | 21° | 15° | 10° |
| °F | 90° | 70° | 60° | 50° |
| 10° | 345 | 385 | 400 | 415 |
| 50° | 761 | 849 | 882 | 915 |
| 21° | 335 | 373 | 390 | 405 |
| 70° | 739 | 822 | 860 | 893 |
| 32° | 320 | 360 | 373 | 385 |
| 90° | 705 | 794 | 822 | 849 |
| 38° | 305 | 345 | 360 | 370 |
| 100° | 672 | 761 | 794 | 816 |



AIR COOLED

WATER COOLED

TOP VIEW



Back View

Back View

- A Water drain Ø20 mm
- B Potable water inlet 3/4 GAS
- C Electrical cable supply
- D Water cooled inlet 3/4 GAS
- E Water cooled outlet 3/4 GAS

