



Sêlç'Ëv|ã  
Q @kO@ãã Áv|\*  
Ö Ä-ä|ä^|ÄF  
FGGEJ/Öv|ã  
Ø } KË JÄDÄHÄÄ | ÄÄÄ ÄGG  
ÖæKË JÄDÄHÄÄ | ÄÄÄ ÄGF  
^T æKä | Ö \æ|c'Äv|ã Ä^  
Qc|} ^ÄQq KQ , Äæ|c'Äv|ã B|{

SPEC SERIES®


REACH-IN SOLID SWING DOOR REFRIGERATOR

model	STG1R-1S
-------	----------



STG1R-1S	
Exterior	Stainless steel door, with matching aluminum sides.
Interior	Aluminum side walls & back. Stainless steel floor & ceiling.
Shelving	(3) Sets 2/1 Gastronorm runners per section. (shelves optional)

plan view



SPECIFICATIONS	
Dimensions	mm.
Length	699
Depth	858
Height	2137
Electrical	
Horsepower	1/2
Amps	3.5
Voltage	230-240/50/1
NEMA	▲ Plug type varies by country
Cord Length	2.74 M.
† Depth does not include 38mm for door handle.	

Specifications subject to change without notice.  
Chart dimensions are rounded up to the nearest whole number. (inches rounded up to the nearest 1/8").



TRUE FOOD INTERNATIONAL, INC. • 2001 East Terra Lane • O'Fallon, Missouri 63366-4434

US Tel: +1 636 240 2400 • US Fax: +1 636 272 7546 • US Toll Free: +1 800 325 6152

Canada Toll Free to USA: +1 800 860 8783 • www.truemfg.com

PROJECT NAME	LOCATION		AIA #
ITEM #	QTY	MODEL #	SIS #

# SPEC SERIES®

REACH-IN SOLID SWING DOOR REFRIGERATOR

model STG1R-1S



## standard features

### REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system using environmentally friendly (CFC free) 134A refrigerant.
- High capacity, factory balanced refrigeration system that maintains cabinet temperatures of 33°F to 38°F (.5°C to 3.3°C) for the best in food preservation.
- State of the art, electronically commutated evaporator and condenser fan motors. ECM motors operate at higher peak efficiencies and move a more consistent volume of air which produces less heat, reduces energy consumption and provides greater motor reliability.
- Top mounted refrigeration system with evaporator positioned out of food zone to maximize capacity.
- Electronic control.

### CABINET CONSTRUCTION

- Insulation - entire cabinet structure and solid door are foamed-in-place using Ecomate. A high density, polyurethane insulation that has zero ozone depletion potential (ODP) and zero global warming potential (GWP).
- 5" (127 mm) diameter plate castors - locks provided on front set.

### DOOR

- Lifetime guaranteed bolt style door lock standard.

- Lifetime guaranteed heavy duty all metal working door handle.
- Positive seal self-closing door with 120° stay open feature. Lifetime guaranteed external cam lift door hinges, four (4) per door section.
- Magnetic door gaskets of one piece construction, removable without tools for ease of cleaning.

### LIGHTING

- LED interior lighting, safety shielded.

### MODEL FEATURES

- Exterior digital temperature display, available with either °F or °C.
- Evaporator epoxy coated to eliminate the potential of corrosion
- Curb mounting ready.

### ELECTRICAL

- Unit completely pre-wired at factory and ready for final connection to a 230-240/50/1 phase dedicated outlet.
- Plug type varies by country.

### OPTIONAL FEATURES/ ACCESSORIES

*(upcharge & lead times may apply)*

- 6" (153 mm) standard legs.
- 6" (153 mm) seismic/flanged legs.
- 6" (153 mm) stainless steel legs.
- Field reversible hinges.
- Additional shelves.
- Stainless back.

### SHELVING KIT OPTIONS

- STG series kits field installed, upcharge applies, lead times may apply.
- Kit #1: Nine (9) sets of #1 type tray slides and pilasters (field installed), bottom support of one (1) 18"L x 26"D (458 mm x 661 mm) pan or two (2) 14"L x 18"D (356 mm x 458 mm) pans.
- Kit #2: One (1) set half-section #2 steel rod tray slides and pilasters (field installed), rim support of one (1) 18"L x 26"D (458 mm x 661 mm) pan.
- Kit #3: Six (6) sets of universal type tray slides and pilasters (field installed), bottom support of one (1) 18"L x 26"D (458 mm x 661 mm) pan, two (2) 14"L x 18"D (356 mm x 458 mm) pans or two (2) 12"L x 20"D (305 mm x 508 mm) pans.
- Kit #4: Three (3) chrome shelves 25"L x 27 ¾"D (635 mm x 705 mm). Four (4) shelf supports included per shelf (field installed); adjustable on 6" (153 mm) increments. Optional wall mounted shelf support pilasters (field installed) with four (4) shelf clips per shelf available; adjustable on ½" (13 mm) increments (must order at time of cabinet order).
- Additional kit option components available individually.

METRIC DIMENSIONS ROUNDED UP TO THE  
NEAREST WHOLE MILLIMETER

SPECIFICATIONS SUBJECT TO CHANGE  
WITHOUT NOTICE