

LMSEY2A19AYE0 *
LMSEY2A25AYE0 *

Max. Kühlleistung

Modell	Nenn-Betriebs- frequenz [Hz]	Außentem- peratur [°C Trockenkugel]	Kühlleistung							
			Kaltraumtemperatur [°C]							
			-25	-20	-15	-10	-5	0	5	10
LMSEY2A19AYE0*	50 Hz	45	705	885	1066	1247	1427	1608	1714	1927
		40	771	692	1152	1342	1532	1722	1912	2102
		35	838	1038	1237	1436	1636	1835	2035	2234
		32	878	1090	1288	1493	1699	1900	2109	2314
		30	905	1114	1323	1531	1740	1949	2158	2367
		25	972	1190	1408	1626	1845	2063	2281	2499
		20	1038	1266	1494	1721	1949	2177	2404	2632
		15	1105	1342	1579	1816	2053	2290	2527	2765
		10	1172	1418	1665	1911	2158	2404	2651	2897
		5	1238	1494	1750	2006	2262	2518	2774	3030
LMSEY2A25AYE0*	50 Hz	45	957	1202	1448	1693	1938	2183	1714	1927
		40	1048	1306	1564	1822	2080	2338	2596	2854
		35	1138	1409	1680	1951	2222	2492	2763	3034
		32	1193	1480	1750	2028	2307	2580	2864	3142
		30	1229	1512	1796	2080	2363	2647	2930	3214
		25	1319	1616	1912	2209	2505	2801	3098	3394
		20	1410	1719	2028	2337	2647	2956	3265	3574
		15	1501	1822	2144	2466	2788	3110	3432	3754
		10	1591	1926	2261	2595	2930	3265	3600	3934
		5	1682	2029	2377	2724	3072	3419	3767	4114

Min. Kühlleistung

Modell	Nenn-Betriebs- frequenz [Hz]	Außentem- peratur [°C Trockenkugel]	Kühlleistung							
			Kaltraumtemperatur [°C]							
			-25	-20	-15	-10	-5	0	5	10
LMSEY2A19AYE0* LMSEY2A25AYE0*	50 Hz	45	414	588	762	936	1110	1284	1458	1632
		40	464	643	821	1000	1178	1357	1535	1714
		35	514	697	880	1063	1246	1429	1612	1795
		32	544	730	915	1101	1286	1472	1658	1843
		30	564	751	939	1126	1314	1501	1688	1876
		25	614	806	998	1189	1381	1573	1765	1957
		20	664	860	1057	1253	1449	1645	1841	2038
		15	714	915	1115	1316	1517	1717	1918	2119
		10	764	969	1174	1379	1585	1790	1995	2200
		5	814	1024	1233	1443	1652	1862	2071	2281